

EN AW-1050A

ASTM 1050 · 1xxx · Toza alyuminiy

BELGILANISHLAR

EN AW EN AW-1050A	ASTM / US 1050	DIAMETRLAR 9.5 mm	Σ, MPA 80-95
-----------------------------	--------------------------	-----------------------------	------------------------

QO'LLANISH SOHASI

Umumiy maqsadli kabellar, shinalar, elektrotexnika sohasidagi o'tkazgichlar.

AFZALLIKLAR

- Yaxshi elektr o'tkazuvchanlik
- Oson ishlash
- Umumiy qo'llanmalar uchun iqtisodiy yechim
- Yuqori plastiklik

YETKAZIB BERISH HOLATLARI

HOLAT	DIAMETR, MM	MUSTAHKAMLIK CHEGARASI, MPA	CHO'ZILISH, MIN, %	SOLISHTIRMA QARSHILIK, MAKS, Ω·MM ² /M	O'TKAZUVCHANLIK, MIN, % IACS
F	9.5	80-95	20	0.02820	61.5
O	9.5	60-85	25	0.02810	61.5
H12	9.5	100-130	12	0.02850	60.8

KIMYOVIY TARKIB, %

BELGILANISHLAR	MIN %	MAX %
Si	—	0.250
Fe	—	0.400
Cu	—	0.050
Mn	—	0.050
Mg	—	0.050
Zn	—	0.070
Ti	—	0.050
B	—	0.050

BELGILANISHLAR	MIN %	MAX %
Al (Al, min)		≥ 99.50%
Boshqa aralashmalar — har biri		≤ 0.03%
Boshqa aralashmalar — jami		≤ 0.10%

Alusilk
PART OF ITS GROUP
Coiled Aluminium · Connected Future

BOSH OFIS
Dubai Silicon Oasis, Dubai, UAE
+971 50 153 0202
info@alusilk.ae

O'ZBEKISTONDAGI FILIAL
Abdulla Qodiriy ko'chasi, 7 · Yunusobod tumani
· Toshkent
+998 97 341 2222
alusilk.uz · alusilk.ae